

MRU H



KONGSBERG



March 2014

THE VERSATILE HEAVE COMPENSATOR

This fifth generation MRU is specially designed for heave compensation applications.

Typical applications

The MRU H is specially designed for motion measurements in marine applications requiring highly accurate heave measurements in environments with extreme horizontal accelerations. This MRU is an ideal sensor for roll, pitch and heave compensation of offshore cranes and echo sounders. The MRU H can also be used on typical ship motion monitoring applications such as helideck motion monitoring, hydroacoustic positioning systems, as well as hull stress monitoring.

Function

The MRU H incorporates three highly accurate accelerometers and three Micro-Electro-Mechanical-Structures (MEMS) angular rate gyros. This unit achieves high reliability by using solid state sensors with no rotational or mechanical wear-out parts.

The unit is delivered with Windows based configuration and data presentation software. In this software vector arms from where the MRU is mounted to center of gravity (CG) and two individually configurable monitoring points (MPs), can be defined. The heave measurements can be output in four different locations (the MRU itself, CG, MP1 and MP2) simultaneously on serial lines or Ethernet port. Typical monitoring point is the transducer head or the crane tip.

Output variables

The MRU H outputs roll, pitch and heave together with linear acceleration in 3-axes. The MRU H outputs heave position, velocity and accelerations in adjustable frames. In addition roll and pitch angles and corresponding angular rate vectors are output.

External inputs

The MRU H accepts input of external speed and heading information on separate serial lines or Ethernet for improved accuracy in heave, roll and pitch during turns and accelerations. For time synchronization the MRU accepts 1-second time pulse (1PPS) input on a TTL line (XIN) or as RS-232/422 signal.

Digital I/O protocols

For this fifth generation MRU data is available through both Ethernet interface and serial lines enabling easy distribution of MRU data to multiple users on board the vessel. Output protocols for commonly used survey equipment are available on two individually configurable serial lines and Ethernet/UDP.

FEATURES MRU H

- High accuracy heave measurements even in dynamic environments
- Outputs on RS-232, RS-422 and Ethernet
- High output data rate (200 Hz)
- Precise heave at long wave periods by use of PFreeHeave® algorithms
- Lever arm compensation to two individually configurable monitoring points
- Meets IHO special order requirements
- Small size, light weight and low power consumption
- No limitation to mounting orientation
- Each MRU delivered with Calibration Certificate
- Selectable communication protocols in the Windows based MRU configuration software
- 2-year warranty



TECHNICAL SPECIFICATIONS

ROLL AND PITCH OUTPUT

Angular orientation range	±180°
Angular rate range	±100 °/s
Resolution roll, pitch	0.001°
Angular rate noise	0.1 °/s RMS
Static ²⁾ accuracy	0.04° RMS
Dynamic ¹⁾ accuracy (for a ±5° amplitude)	0.05° RMS
Scale factor error	0.2 % RMS

HEAVE OUTPUT

Output range	±50 m
Periods (real-time)	0 to 25 s
Periods (delayed)	0 to 50 s
Heave accuracy (real-time)	5 cm or 5 %, whichever is highest
Heave accuracy (delayed)	3 cm or 3 %, whichever is highest

ACCELERATION OUTPUT

Acceleration range	±30 m/s ²
Acceleration noise ²⁾	0.002 m/s ² RMS
Acceleration accuracy	0.01 m/s ² RMS

ELECTRICAL

Power requirements	10 to 36 V DC, max. 12 W
Serial ports:	
Com1	Bidirectional RS-422
Com2	Bidirectional RS-422 from junction box, user configurable RS-232, RS-422
Com3 & Com4	Input only, user configurable RS-232, RS-422
Analog channels (junction box)	# 4, ±10 V, 14 bit resolution

Specifications subject to change without any further notice.

Ethernet ports	Three output and one input
Ethernet UDP/IP	10/100 Mbps
Digital output variables	24 (max), serial or Ethernet
Output data rate (max)	200 Hz
Timing	<1 ms

ENVIRONMENTAL SPECIFICATIONS

Temperature range	-5 °C to +55 °C
Humidity range, electronics	Sealed, no limit
Enclosure protection	IP-66
Vibration	IEC 60945/EN 60945

ELECTROMAGNETIC COMPATIBILITY

Compliance to EMCD, immunity/emission	IEC 60945/EN 60945
---------------------------------------	--------------------

OTHER DATA

MTBF (computed)	50000 h
Housing dimensions	Ø 105 x 140 mm (4.134" x 5.525")
Material	Anodised aluminium
Weight	2.4 kg
Connector	Souriau 851-36RG 16-26S50

DATA OUTPUT PROTOCOLS

- MRU normal	- Atlas Fansweep
- NMEA proprietary	- TSS1
- Souder	- Seapath binary 23
- EM3000	- PFreeHeave®

1) When the MRU is exposed to a combined two-axes sinusoidal angular motion with 10 minutes duration.

2) When the MRU is stationary over a 30-minute period.