



CSP-SNv1250 Seismic Energy Source



The **CSP-SNv** is built on the proven high voltage technology of the industry leading CSP range of power supplies. Incorporating microprocessor control and configuration for greater configuration flexibility and reliability whilst retaining a fail-safe logic design.

The CSP-SNv provides a solution to the industry requirement of acquiring UHR seismic data in challenging environments with a $\leq 1m$ shot point interval. The 4000 Joule per second peak charge rate delivered from a single phase AC voltage supply allows repetition rates less than 0.4s at 1000 Joule output.

The CSP-SNv has been engineered for use with the dual deck Dura-Spark UHD 400+400 catamaran, providing flip-flop and fire delay modes of operation.

Key Features

- Microprocessor configuration and control.
- Intuitive user interface, with LCD display and LED indicators.
- 4000J per second peak charge rate
- Fire delay mode
- Flip-flop mode
- User programmable 'soft start'
- Master / slave key support
- Additional safety/protection features
- Programmable voltage technology allows operator tuning to suit application
- High current and voltage solid state (semiconductor) discharge method
- Debug log and diagnostics.
- Meets EC emissions regulations enabling interference-free field use
- Supplied in robust transit case, with HV junction box (HVJ3004) and mains lead.

Technical Specification

PHYSICAL

Size	Transit Case, 19" rack, 11U high
Weight	CSP-SNv1250, case and cover: 90kg

ELECTRICAL SPECIFICATION

Mains Input	240VAC 45-65Hz@ 6.0kVA single phase. 3 pin connector Variable Input Power Circuitry (AVIP) 'soft start' control
-------------	--



CSP-SNv 1250 Technical Specification

Voltage Output	3536 to 3953VDC, 4 pin interlocked connector Solid state semi-conductor discharge method
Output Energy	Easy switch selectable in increments CSP-SNv1250 100, 200, 300, 400, 500, 600, 700, 800, 900, 1000 Joules 125, 250, 375, 500, 625, 750, 875, 1000, 1125, 1250 Joules
Charging Rate	4000J/second for continuous operation at 0-45°C
Capacitance	CSP-SNv1250 176µF @ 10 ⁸ shot life
Trigger	User configured: External: +ve key (5-12Vdc), -ve key or isolated closure (CSP and Remote unit) Internal: User defined Manual: Key press Fire Delay option Flip Flop mode Opto isolated BNC connector on front panel and remote box (optional)
Repetition rate	User configured: External: 6pps maximum. Internal: 200ms to 9975ms Limited by charge rate, energy level and sound source rating
Earth	M8 stainless steel stud on front panel

SAFETY FEATURES

- Main microprocessor control circuits with fail-safe layer of logic circuitry
- LCD display with system status information, configuration
- Specially designed HV connector with interlock
- High speed dump resistors for high voltage components
- Capacitor bleed resistors
- HV output open circuit shutdown
- Trigger monitoring with time out and over clock shutdown
- HV output current monitor and shutdown
- Supply Voltage monitoring and shutdown
- High Voltage monitoring
- Over temperature shutdown
- Cover and connector interlocks
- Diagnostic log download for improved support
- Remote unit available to configure, trigger and operate remotely

*The unit's internal design has a modular construction for ease of servicing and capacitor replacement. However, for safety reasons, **only** Applied Acoustics trained engineers should attempt a repair.*

COMPATIBLE SOUND SOURCES

CSP-SNv1250 Dura-Spark UHD 240/400, Dura-Spark 400+400, S-Boom triple plate boomer

OPTIONS

- Remote unit Allows operator to control CSP at a distance. Includes Key In and Key Out.
- Field spares kit For trained technicians only. For servicing units in the field.



APPLIED ACOUSTICS
Underwater Technology
An AAE Technologies Group Company

Due to continual product improvement, specification information may be subject to change without notice.
CSP-SNv1250 Seismic Energy Source/April 2020
©Applied Acoustic Engineering Ltd.



Applied Acoustic Engineering Ltd
Marine House, Marine Park
Gapton Hall Road
Great Yarmouth NR31 0NB
United Kingdom

T +44(0)1493 440355
F +44(0)1493 440720
E general@appliedacoustics.com
W www.appliedacoustics.com