

CHCNAV

CTS-112R₄

**TOTAL
STATION**



**SURVEYING &
ENGINEERING**



COST-EFFECTIVE EASY TO USE TOTAL STATION

The CTS-112R4 total station is based on proven technologies and designed for users who need the most cost-effective survey solution. It has an angle accuracy of 2" and integrates a high efficiency EDM to provide measurement range of 1000 m reflectorless and up to 5 000 m using a single prism, with millimeter accuracy.

Each replaceable battery provides 8 hours continuous working time, so you do not have to worry about losing power in the field anymore.

TOTAL STATION USE MADE EASY

Best-in-class industrial design with dual face keyboards and built-in laser plummet.

Dual face keyboards with buttons illumination to minimize mistakes provide optimum viewing and convenience under any environmental conditions. Built-in laser plummet allows quick instrument setup in all lighting conditions.

HIGH EDM PERFORMANCES

Up to 1000 m reflectorless measurement range.

The CTS-112R4 is one of the fastest total stations in its class, with a distance measurement speed of 0.3 seconds. Reflectorless range is up to 1000 m and distance measurement to single prism is up to 5000 m.

INTUITIVE ONBOARD SOFTWARE

Bring productivity to any typical survey and construction projects.

The CTS-112R4 is a versatile, easy to use, rugged total station with a variety of advanced field applications software built-in to make your work more efficient.

EXTENDED MEMORY CAPACITY

Store up to 30,000 points in internal memory.

Adding external SD card up to 32 GB will boost record capacity to 245,760,000 points.



2" ACCURACY
1000 M
REFLECTORLESS




MAKE
FIELD SURVEY EASY

SPECIFICATIONS

Distance Measurement	
Laser output	Prism: Class 2 Reflective sheet: Class 2 Non-prism: Class 3R
Distance measurement	Prism: 5000 m Reflective sheet: 1000 m Non-prism: 1000 m
Accuracy	Prism: 2 mm + 2 ppm Reflective sheet: 3 mm + 2 ppm Non-prism: 3 mm + 2 ppm
Measuring time	Prism fine: 0.3 s Prism tracking: 0.1 s
Laser type	Red visible laser
Carrier	0.650–0.690 μm
EDM type	Coaxial
Resolution	0.1 mm
Angle Measurement	
Diameter	79 mm
Minimum readout	0.1"/1"/5"/10" optional
Accuracy	2"
Detection method	Horizontal: Dual / Vertical: Dual
Telescope	
Image	Erect
Tube length	154 mm
Objective lens effective	For telescoping: 45 mm
aperture	For measuring: 50 mm
Magnification	30
Field of view	1°30'
Minimum focus distance	1.4 m
Resolving power	3"
Reticle illumination	4 brightness levels
Auto Compensator	
System	Dual axis photoelectric detection
Working range	± 3'
Accuracy	1"
Laser Plummet	
Accuracy	1.5 mm at 1.5 m instrument height
Laser spot size	2.5 mm

Display	
Type	LCD, 6 lines digital screen
Keyboard	Alphanumeric, 28 keys with backlight
Control panel	Double
Screen size	2.8 inch
Interface and Data Recording	
Interface	RS232-C, Mini-USB, SD
Internal storage	4 MB (ready for 30,000 points)
External storage	Up to 32 GB (ready for 245,760,000 points)
Battery	
Battery type	Rechargeable lithium battery
Battery voltage	DC 7.4 V 3100 mAh
Operating time	Continuous distance/angle: 8 hours Continuous angle-only: 16 hours
Charging time	About 3 hours
Environment	
Operating temperature	-20°C to +50°C (-4°F to 122°F)
Dust and water proof	IP55
Size and Weight	
Size	160 x 150 x 330 mm (6.3 x 5.9 x 13.0 in)
Weight	5.2 kg

*All specifications are subject to change without notice.



© 2020 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision January 2021.

WWW.CHCNAV.COM | SALES@CHCNAV.COM

CHC Navigation Headquarter
Shanghai Huace Navigation Technology Ltd.
599 Gaojing Road, Building D,
Shanghai, 201702, China,
+86 21 54260273

CHC Navigation Europe
Infopark Building, Sétány 1, 1117
Budapest, Hungary
+36 20 235 8248 +36 20 5999 369
info@chcnav.eu

CHC Navigation USA LLC
16412 N 92nd Street, Suite 115,
85 260 Scottsdale, Arizona, USA,
+1 480 676 4306

CHC Navigation India
409 Trade Center, Khokhra Circle,
Maninagar East, Ahmedabad,
Gujarat, India
+91 90 99 98 08 02