



# WAVEGUIDE DIRECTION WG5 SERIES

Remote monitoring of wave direction, wave height, wave period and tide

The new WaveGuide is the latest and most technically advanced radar from Radac. This accurate wave monitoring system is an easy to use, reliable and robust device to measure tide, wave direction, wave height and wave period. The new radar is capable of maintaining a high level of precision and accuracy in harsh environmental conditions and is particularly suited to marine and offshore installations.

## KEY FEATURES

- 0 - 360° wave direction
- 0 - 60 m wave height
- Highly accurate
- Maintenance free
- Optional ATEX / IECEx

## NEW FEATURES

- Measuring at 10 Hz
- Network connected

With an array of three radars, the elevation of the sea surface is measured at three positions. These positions form a virtual triangle at the water surface by pointing one radar perpendicularly downwards and tilt the other two. Knowing the slope of the water surface and the phase relations between the three positions, the wave direction can be calculated.

The radars measure the distance to the water surface 10 times per second. In all wind and wave conditions the accuracy for water level is proven to be below 1 cm. The wave data are sent to the processing unit via a network link. The processing unit facilitates data acquisition, data processing, data presentation and remote service. Data can be locally stored on an external USB drive, or distributed through two serial ports as well as over the network. Any device connected to the (private) network can access the web-based user interface.



Elektronicaweg 16b  
2628 XG Delft  
The Netherlands  
T +31 15 890 32 03  
info@radac.nl  
www.radac.nl

We are a Dutch company, based in Delft. Since 1996, we develop, manufacture and market the WaveGuide. We are proud that our professional systems are trusted across the industry. Our main clients include oil companies, offshore wind farm operators, port operators and shipping companies.

# WAVEGUIDE DIRECTION

## WG5 SERIES

### SPECIFICATIONS

Heave	Range: 2 - 75 m to surface Accuracy: $\pm 3$ mm <sup>1)</sup> Frequency: 10 Hz
Water level	Accuracy: $\pm 1$ cm <sup>2)3)</sup> Processing: 10 sec, 1 min, 5 min or 10 min Interval: 1 min
Wave height	Range: 0 - 60 m Accuracy: $\pm 1$ cm <sup>3)</sup> Processing: SWAP <sup>4)</sup> (per 20 min data block) Interval: 1 min
Wave period	Range: 1 - 100 s Accuracy: $\pm 50$ ms <sup>3)</sup> Processing: SWAP <sup>4)</sup> (per 20 min data block) Interval: 1 min
Wave direction	Range: 0 - 360° Accuracy: $\pm 2^\circ$ <sup>3)</sup> Processing: SWAP <sup>4)</sup> (per 20 min data block) Interval: 1 min

#### COMPACT VERSION: WG5-DR-CP (includes 3 radars + 1 processing unit)

##### Specifications per radar

Mechanical	Dimensions: $\varnothing$ 265 x 245 mm Weight: 12.5 kg Material: Stainless steel, AISI 316L
Electrical	Power: 24 - 64 VDC, 65 - 240 Vac, 8 W Frequency: 10 GHz (X-band) Modulation: Triangular FMCW Emission: 0.1 mW max. (Far below acceptable limits for exposure to the human body)
Environmental	Temperature: -40 °C to 65 °C Humidity: 0 - 100 % Ingress Protection: IP67



#### EXPLOSION PROOF VERSION: WG5-DR-EX (includes 3 radars + 1 processing unit)

##### Specifications per radar

Mechanical	Dimensions: 217 x 319 x 379 mm (d x w x h) Weight: 14.4 kg (excl. antenna 2.8 kg) Material: Chromatized aluminum
Electrical	Power: 24 - 65 VDC, 65 - 240 Vac, 8 W Frequency: 10 GHz (X-band) Modulation: Triangular FMCW Emission: 0.1 mWatt max. (Far below acceptable limits for exposure of the human body)
Environmental	Temperature: -40 °C to 65 °C Humidity: 0 - 100 % Ingress Protection: IP67 Safety: ATEX, II 1/2 G Ex d [ia Ga] IIB T6 Ga/Gb



##### Processing unit

Dimensions:	170 x 172 x 85 mm (d x w x h)(19" rack mounting available)
Com ports:	2x RS232
Network:	3x Ethernet
USB:	2x USB 2.0
Power:	24 - 48 VDC, 4.8 W
Temperature:	-20 °C to 65 °C
Cooling:	No fan required



1) Valid for a still water surface.

2) For a water surface with waves.

3) The accuracy of the wave parameters is not limited by the radar sensor, yet it is defined by the stochastic nature of sea-surface measurements.

4) SWAP is the Standard Wave Analysis Program, in accordance with the applied standards of the Dutch Ministry of Infrastructure and Environment and of the International Association of Oil and Gas producers.

